



HONDA ECT 7000 Petrol Single / Three Phase Generator max. 7 kW

Product description:

When it comes to a generator on a construction site, you don't want to cut corners on quality. Always choose a Honda for those jobs that need to be done with minimum fuss. They're tough and always ready to go.

Plenty of energy

Simplicity and cost effectiveness go hand in hand with a condenser/inductive type EC generator. The power produced is perfect for resistive loads like power drills, circular saws and concrete breakers.

LET'S START WORK

Just fire it up and forget it.

Quick and easy: the accessible ergonomic fuel filler cap is right where you need it – on top. Practical sockets and controls make starting and running the generator quick and simple. Just start it and let it get on with the job, because the unique Oil Alert™ will automatically switch off the ignition if the oil drops below a safe level. It's as safe as safe can be.

Smooth running

Honda has built an engine mount system into the durable steel frame. These rubber shock absorbers are positioned either side of the engine at 45° and significantly reduce the engine vibration of an already quiet machine.

The photos are for illustrative purpose only.





Product features:

Phase: Single phase / Three phase
Maximum power single phase (KW): 4
Continuous power single phase (KW): 3.6
Maximum power single phase (KVA): 5
Continuous power single phase (KVA): 4.2
Maximum power three phase (KW): 7
Continuous power three phase (KW): 6.5
Maximum power three phase (KVA): 8.75
Continuous power three phase (KVA): 8.12
Fuel: Gasoline
Frequency (Hz): 50
Voltage (V): 230 / 400
Sockets configuration: 1 x 400V CEE - 2 x 230V SCHUKO
Engine: Honda GX390 T1, 4 stroke, OHV
Engine rpm (rpm): 3000
Ignition: Transistorized
Starting system: Manual
Engine capacity (cm³): 389
Number cylinders: 1
Oil capacity (L): 1.1
Cooling: Air
Alternator: Tripolar
Bore x stroke (mm): 88 x 64
Fuel tank capacity (L): 6.2
Consumption (L/h): 2.75
Running time (h): 2.25
Acoustic power: 97 dB(A)
Acoustic pressure: 86 dB(A)
Length (mm): 800
Width (mm): 550
Height (mm): 540
Dry weight (Kg): 77
Silenced: No
Super silenced: No
Product type: Generator
ATS Switch device : No
Voltage regulator: Compound
Engine manufacturer: Honda
Video: V0JyzKGrpJE

