



TECNOGEN LW16000TSS/A GENERATOR WITH SEPARATE AUTOMATIC PANEL

Product description:

TECNOGEN LW16000TSS/A GENERATOR WITH SEPARATE AUTOMATIC PANEL

Electric start diesel generators, water-cooled, 3000 rpm, available in both single-phase and three-phase versions, with powers from 11.7 to 34.7 kVA MAX. Sturdy and reliable, they are suitable to operate for long periods despite the high rotation rate. The set-up relative to the base-mounted versions includes a built-in fuel tank with a capacity of 52 l, a metal grille placed to protect the radiator and a professional electrical panel, entirely made of ABS with a high degree of protection, equipped with instruments that respect the strictest safety standards. The silenced models are also equipped with a soundproofed canopy in hot-dip galvanized steel. The generators of the W 3000 series are the ideal choice for applications with automatic intervention panel or for use in the mechanical / industrial field.

The image is purely indicative.

Product features:

Phase: Single phase / Three phase

Maximum power single phase (KW): 4.7

Maximum power single phase (KVA): 5.8

Maximum power three phase (KW): 14

Maximum power three phase (KVA): 17.5

Fuel: Diesel

Frequency (Hz): 50

Voltage (V): 230 / 400





Engine: HONDA GC160
Engine rpm (rpm): 3000
Starting system: Electric
Engine capacity (cm³): 1028
Number cylinders: 3
Cooling: Water
Fuel tank capacity (L): 54
Consumption (L/h): 3.5
Running time (h): 15.4
Acoustic power: 94 dB(A)
Length (mm): 1750
Width (mm): 770
Height (mm): 1070
Dry weight (Kg): 405
Silenced: No
Super silenced: Yes
ATS Switch device : Yes
Voltage regulator: Compound / AVR (optional)
Engine manufacturer: Lombardini