



MOSA GE 165 PSX

Product description:

MOSA GE165 PSX 132 KW generating set

MOSA GE165 PSX three-phase 132 KW generator set with Perkins diesel engine. The MOSA GE165 PSX generator set is equipped with electric start. The alternator of the MOSA GE165 PSX generator set is synchronous, three-phase, self-excited, self-regulated, brushless with class H insulation with AVR voltage regulator.

This MOSA is compact and convenient to maneuver and transport thanks to its compact size, with a weight of 2230 kg in addition to its practical drillable base. The MOSA GE165 PSX generator set with 230-liter fuel tank has a fuel consumption of 24.7 liters/hour at 75% load for an autonomy of more than 9 hours.

Technical specifications:

Three-phase output Stand-by (LTP): 165 kVA (132 kW) / 400V / 238.1 A

Three-phase output PRP: 150 kVA (120 kW) / 400V / 216.5 A

Frequency: 50 Hz

Cos φ: 0.8

ENGINE TECHNICAL DATA

Model: PERKINS 1106A - 70TAG2

Cylinders / Displacement: 6/ 7010 cm³ (7.01 lit.)

Bore / Stroke: 105 / 135 (mm)

Compression ratio: 18.2 : 1

Net stand-by output: 144 kW (196 hp)

Net PRP output: 131 kW (178 hp)

BMEP Effective average pressure LTP - PRP: 1702 kPa - 1552 kPa

RPM controller: Mechanical

110 % (Stand-by power): 201.1 g/kWh - 36.1 l/h

100 % PRP: 203.3 g/kWh - 33.4 l/h

75 % PRP: 199.7 g/kWh - 24.7 l/h

50 % PRP: 197.9 g/kWh - 16.4 l/h

Cooling system: Liquid

Total capacity - motor only: 21 l - 9.5 l





Fan air flow: 282 m³/min.
Total oil capacity: 16.5 l
Sump oil capacity: 12.4 l (min) - 14.9 l (max)
Full load oil consumption: Maximum exhaust gas flow rate: 25.53 m³/min.
Max. exhaust gas temperature: 484 °C
Max. back pressure: 6 kPa (0.06 bar)
Electrical system: 12 Vdc
Starter motor power: 4.2 kW
Battery charging alternator capacity: 65 A
Cold start: - 10 °C
With cold start device: - 20 °C
Air filter: Dry
Combustion air flow: 10.67 m³/min.
From exhaust: 105.6 kW
From water and oil: 75.7 kW
Injected to environment: 12.2 kW
Supercharger cooling: 20.5 kW

TECHNICAL DATA ALTERNATOR

Continuous power: 165 kVA
Standby power: 180 kVA
Three-phase voltage: 380-415 Vac
Frequency: 50 Hz
Cos φ: 0.8
A.V.R. model.: MARK I
Voltage regulation accuracy: ± 0.5 %
Sustained short circuit current: 3 I_n
Transient Cdt (100% of load): Response time: Yield at 100% load: 92.9 % (400V - Cos φ 0.8)
Isolation: Class H
Connection - Terminals: Star - No. 12
Electromagnetic Compatibility: EN55011
Harmonic Distortion - THD: Telephone Interference - THF: Direct Synchronous - X_d: 280 %
Direct Transitory - X'_d: 24 %
Direct Subtransitory - X''_d: 13.5 %
Synchronous in quad. - X_q: 135 %
Subtrans. in quadrature - X'_q: 14.9 %
Of reverse sequence - X₂: 14.2 %
Of zero sequence - X₀: 2.9 %
Transitory - T'_d: 0.09 sec
Subtransitory - T''_d: 0.011 sec
Unidirectional - T'_{do}: 0.95 sec
Unidirectional - T_a: 0.012 sec
K_{cc} short-circuit ratio: 0.47
Cooling air flow rate: 0.42 m³/sec.
Coupling | Bearings: Direct SAE 3 - 11 ½ - No. 1





GENERAL SPECIFICATIONS

Tank capacity: 230 lt.

Run time (75% of PRP): 9.5 h

Measured acoustic power LwA: 94 dB(A) (69 dB(A) @ 7m)

Guaranteed acoustic power LwA: 96 dB(A) (71 dB(A) @ 7m)

Performance class: G2

Length: 3400 mm

Width: 1200 mm

Height: 1800 mm

Weight: 2230 Kg

MOSA GE165 PSX - Perkins diesel engine electric start - Three-phase alternator - Three-phase power 150 kVA (120 kW)

Features:

- Electronic AVR voltage regulation
- Oil extraction pump
- Large access doors to allow easy maintenance (change air filters, oil, fuel filters)
- Central lifting hook
- Control panel with digital control unit in Automatic or Manual version
- Sealed basement that can contain any leakage of liquids in the engine avoiding environmental pollution
- Supersilenced
- Complies with EC directives for noise and safety

If you are looking for another product like the Generating Set MOSA GE165 PSX then you can see on our catalog other terrestrial generators.

Images and technical data are not binding.

Product features:

Phase: Single phase / Three phase

Continuous power single phase (KW): 44

Continuous power single phase (KVA): 55

Maximum power three phase (KW): 132

Continuous power three phase (KW): 120

Maximum power three phase (KVA): 165

Continuous power three phase (KVA): 150

Fuel: Diesel

Frequency (Hz): 50

Voltage (V): 230 / 400

Engine: PERKINS 1106A-70TAG2, 4 stroke turbo-aftercooler





Emissions Regulations: Stationary Use

Engine rpm (rpm): 1500

Starting system: Electric

Engine capacity (cm³): 7010

Number cylinders: 6

Cooling: Water

Inyección : Direct

Alternator: Sincrono trifase, autoeccitato, autoregolato, senza spazzole

Fuel tank capacity (L): 230

Consumption (L/h): 24.7 at 75% of the load

Running time (h): 9.3 at 75% of the load

Acoustic power: 94 dB(A)

Acoustic pressure: 69 dB(A) at 7 m

Length (mm): 3400

Width (mm): 1200

Height (mm): 1800

Dry weight (Kg): 2230

Silenced: Yes

Super silenced: Yes

Product type: Generator

ATS Switch device : Optional

Voltage regulator: AVR

Engine manufacturer: Perkins

