



HONDA Outboard BF 2.3 SCHU 41 cm Shaft 1.7 kW 2.3 Hp 57 cm³

Product price:

717,00 € tax excluded

Product description:

HONDA BF2,3SCHU Outboard Shaft 41cm 1.7 kW 2.3 Hp 57 cm³

Honda BF2,3SCHU is an outboard engine powerful enough to take you into coastal waters on an inflatable boat or dinghy. Lightweight to carry, they include ergonomic handles and can be easily stored in the trunk of your car.

The smallest of the Honda outboards is very easy to use. Unlike 2-stroke engines, it's quiet and you don't have to worry about the mixture of oil and gasoline. So you can accelerate to the middle of a lake, up a river or cruise along the coastal strip of the sea.

The Honda BF2,3SCHU has single-cylinder 4-stroke engines with a top valve. They are easy to start with a manual system that allows the outboard to spin freely right away. Honda BF2,3SCHU outboards have the most advanced technology that precisely controls the ignition phase, so when you start it, even when cold, it will start without hesitation. The air-cooled BF2,3SCHU provides great maneuverability with 360-degree rotation and an integrated fuel-saving space tank.

A centrifugal clutch allows the engine to idle without operating the propeller blades. When you want to start moving, just act on the throttle knob, the clutch engages and drives the propeller a bit like it does in an automatic transmission.

It is very important for a small boat to be agile and able to change direction quickly. The small BF2,3SCHU has a fast turning action, which is perfect for reversing without changing gears. Simply turn the rudder 180° and the boat is able to move in reverse.

Once securely mounted to the boat, you'll find that these outboards are very lightweight and easy to pull out of the water by tilting them. This way you avoid damaging your motor propellers when moving through shallow water or on shore. You can quickly get moving again by acting on the spring system that allows you to lock the motor for safety.





These outboards are the lightest in their class, so it's no wonder they're easy to pull out. They've been made easier to carry, with an ergonomic handle positioned at just the right balance point, allowing you to walk normally without effort.

The sleek design has been taken care of throughout, right down to the slim gearbox that reduces drag in the water while promoting fuel economy.

The knob gives a remarkably smooth feel and is equipped with a screw-clutch that allows it to be locked at various speeds, thus relaxing your hand.

Improving the quality of our lives means, above all, taking care of the environment in which we live. We cannot allow boat fuel to pollute the marine environment. That's why Honda has made outboard engines cleaner, quieter and more environmentally friendly with the introduction of 4-stroke.

First, the aluminum housing is anodized using Honda's patented BF2,3SCHU "double seal" process (1). Then a layer of epoxy primer is applied (2) before silver gloss paint (3). As additional UV protection, a clear resin (4) is applied as a top coat. For added safety, a sacrificial anode is applied to all waterproof connectors.

Technical specifications Honda BF2,3SCHU outboard:

Net Power (kW): 1.7
Net Power (Hp): 2.3
Displacement: 57 cm³
Shank length: Short
Dry weight (Kg): 13.5
Starting: Manual
Ignition system: Transient
Setup and engine lifting: Manual / Manual 4 positions
Transom height (mm): 418
Length (mm): 410
Width (mm): 280
Height (mm): 945
Bore x stroke: 45 x 36 mm
Engine Brand: Honda
Engine Type: OHV, 4 stroke
Number of cylinders: 1
Speed at full throttle (rpm): 5000-6000
Cooling system: Air

Are you looking for an outboard with different technical characteristics? [HERE](#) you can find the whole range Honda or other brands specializing in the field.

Images are purely indicative.





Product features:

Fuel: Gasoline

Engine: OHV, 4 stroke

Ignition: Transistorized

Starting system: Manuale

Engine capacity (cm³): 57

Number cylinders: 1

Cooling: Air

Bore x stroke (mm): 45 x 36

Reduction ratio: 2.42

Rpm at full throttle (rpm): 5000 - 6000

Appearance and engine lifting: Manual / Manual 4 position

Transom height (mm): 418

Net power (kW): 1.7

Fuel tank capacity (L): 1.1

Length (mm): 410

Height (mm): 945

Dry weight (Kg): 13.5

Shaft Length: S

Controls: None

