



HONDA Outboard BF 20 LRTU 56 cm Shaft With Remote 14.9 kW 350 cm³

Product price:

3.885,00 € tax excluded

Product description:

HONDA OUTBOARD BF20DK2 LRTU SHAFT 56CM

Honda BF20DK2 LRTU is an incredibly practical and portable 15 or 20 horsepower outboard engine with well-placed retractable handles. They are perfect for any boat that needs power in a small size.

The engine that comes with the Honda BF20DK2 4-stroke stays quiet both when starting and when increasing its power; they are so quiet that you can take them to their full power, without having to raise your voice to speak. Honda's unique vibration-absorbing rubber mounting system gives a great impression of smoothness.

During forward travel, the Honda BF20DK2's propeller is driven normally through the water, as with all marine engines. In the reverse direction, however, Honda engines make all the difference. This unique reverse exhaust system directs bubbles out of the propeller so it can "grip" the water. The result is immediate response and very precise control.

Honda BF20DK2 LRTU with manual start is available in the version with electric start allow lifting and lowering, allowing you to adjust the trim of the boat to always get the best in performance and fuel efficiency. This also prevents damage to the propeller blades when the boat is close to rocks or shallow water.

Honda BF20DK2 LRTU outboards have a reverse lever that allows you to shift gears with your fingertips. Everything is much easier to use and better positioned than other outboards even for left-handed people. In addition, the soft-grip, twist-lock throttle grip minimizes operating effort, increasing handling.

Honda BF20DK2 LRTU outboards are available with rudder and remote control options. The remote control option displays warning lights for engine, oil pressure and overheating. It also generates an audible signal to get your attention in case anything happens while you're focusing





on other tasks.

Honda BF20DK2 LRTU is anodized the aluminum housing using Honda's patented "double seal" process. Then a layer of epoxy primer is applied before the silver gloss paint. As additional UV protection, a clear resin is applied as a top coat. For added safety, a sacrificial anode is applied to all waterproof connectors.

TECHNICAL CHARACTERISTICS HONDA BF20DK2 LRTU

Net Power (kW): 14.9
Net Power (Hp): 20
Displacement: 350 cm³
Shaft length: Long
Dry weight (Kg): 58.5
Starter: Electric / Manual
Ignition system: Electronic PGM-IG
Type of control Remote
Setup and engine lifting: Manual / Manual 5 positions
Transom height (mm): 563
Length (mm): 650
Width (mm): 350
Height (mm): 1240
Bore x stroke: 59 x 64 mm
Engine Brand: Honda
Engine Type: OHV, 4 stroke
Number of cylinders: 2
Speed at full throttle (rpm): 5000-6000
Cooling system: Water
Battery charge capacity (A): 6
Propeller Rotation: Standard

Are you looking for an outboard with different technical characteristics? Here you can find the entire Honda range or other brands specializing in the field.

Images are indicative only.

Product features:

Fuel: Gasoline
Engine: OHV, 4 stroke
Ignition: Electronic PGM-IG
Starting system: Manual / Electric
Engine capacity (cm³): 350





Number cylinders: 2

Cooling: Water (with thermostat)

Bore x stroke (mm): 59 x 64

Reduction ratio: 2.08

Rpm at full throttle (rpm): 5000 - 6000

Appearance and engine lifting: Manual / Manual 5 position

Transom height (mm): 563

Net power (kW): 14.9

Fuel tank capacity (L): 12

Length (mm): 650

Width (mm): 350

Height (mm): 1240

Dry weight (Kg): 58.5

Shaft Length: L

Controls: Remote