
PRAMAC PMi 2000 SINGLE-PHASE GENERATOR 2KW WITH INVERTER

Product description:

PRAMAC PMi2000 SINGLE-PHASE GENERATOR 2KW WITH INVERTER

The PRAMAC PMi2000 single-phase generator is capable of delivering a maximum power of 2KW, super quiet thanks to the inverter provided.

The PRAMAC PMi2000 is gasoline-powered with a 4-stroke engine, particularly compact and light, it can be easily transported by hand to any place; this feature is very appreciated by those customers who sell their products in squares, streets or markets and who, due to the lack or distance of parking for their cars, must carry the generator by hand for considerable distances (historical center, uncomfortable areas, etc.).

The reduced measures and the strong handle situated above the machine body, make it perfect for a transport and an easy collocation during the periods of inactivity. All the materials used for the manufacture of PRAMAC are of first choice, offering and guaranteeing the customer a tested and proven product at a very convenient price. Precisely for this reason, it is a very popular tool for professionals and DIY enthusiasts.

Thanks to the electrical stabilizer of the Inverter technology that works at very low distortion, the generator delivers constant current loads without voltage spikes that could damage electrical and electronic devices.

Another advantage of the inverter is to work with variable engine speed, according to the need for current to be delivered, optimizing the best fuel consumption, gas emission and wear of mechanical parts. This product is ideal for use in campsites, campers and for outdoor leisure time.

Thanks to the low noise impact obtained thanks to the inverter, it is possible to use the PRAMAC PMi2000, even in environments where particularly loud noises cannot be accepted,



such as historical centers, hospitals, schools, gyms, etc.. Do not underestimate the considerable discomfort that you feel, to be all day near the noisy generators for work necessity.

Technical characteristics PRAMAC PMi2000

Phase Type: SinglePhase
Continuous SinglePhase Power: 2.2 KVA / 1.7 KW
Maximum SinglePhase Power: 2.5 KVA / 2 KW
VAC Voltage: 230 V
Frequency (Hz): 50
Voltage Regulator: INVERTER
Starting Gear: Manual Pull-Out
Engine: OHV 4-stroke
Emission Standard: Stage V
RPM: Variable
Power supply: Gasoline
Fuel tank capacity: 3.5 l
Consumption @ 75 % load: 1.2 l/h
Autonomy @ 75 % load: 3 h
Sound pressure: 61 dB(A) @ 7m
Length: 535 mm
Width: 305 mm
Height: 460 mm
Net weight: 22 Kg

Are you looking for a generator with different technical characteristics? [HERE](#) you can find the area dedicated to PRAMAC generators or other specialized brands

Images and technical data are not binding and may be subject to revisions.

Product features:

Phase: Single phase
Maximum power single phase (KW): 2
Continuous power single phase (KW): 1.7
Maximum power single phase (KVA): 2.5
Continuous power single phase (KVA): 2.2
Fuel: Gasoline
Frequency (Hz): 50
Voltage (V): 230
Sockets configuration: 2 x 230V SCHUKO
Engine: 4 Tempi
Emissions Regulations: Stage 5





Engine rpm (rpm): Variable
Speed governor: Mechanical
Ignition: Recoil
Starting system: Pull starter
Cooling: Air
Fuel tank capacity (L): 3.5
Consumption (L/h): 1.2
Running time (h): 3
Acoustic pressure: 61 dB(A) at 7 m
Length (mm): 305
Width (mm): 535
Height (mm): 460
Dry weight (Kg): 22
Silenced: Yes
Super silenced: Yes
ATS Switch device : No
Voltage regulator: Inverter
Video: 7wIJO_8eyf0

