



PRAMAC LIFTER ELECTRIC STACKER LX16/29

Product price:

8.392,30 € tax excluded

Product description:

The LX II edition is a strong and reliable partner which bridges the gap between lowduty and heavy duty material handling daily operations. Due to its durability, low maintenance LX is suitable for environments as logistic centers, terminals, production and manufacturing areas. Also the new tiller arm equipped with fork lifting and lowering proportional control improves user-friendliness and maneuverability of the truck.

ZAPI controller

AC technology guarantees more energy efficiency and longer battery charging duration, thus reducing maintenance cost. Furthermore the absence of brushes in the motor and the simpler motor structure increase system reliability.

Tiller and controls

Improved tiller with lifting/lowering proportional controls. Fully integrated system with throttle, safety pushbutton, horn, hourmeter, battery status indicator and turtle button.

Maneuverability

The overall width has the same size than the EuroPallet (800 mm) allow the unit to work in narrow spaces and corridors, increase maneuverability and reducing the turning radius.

Visibility

The wide mast and central driving position allow to have a great operator visibility.

Battery compartment

The separate battery compartment allow the installation of high capacity battery (225Ah - 300Ah). The battery inspection is easy and comfortable through the battery cover with hinges. As option automatic battery refilling system can be supplied as the external high frequency battery charger that can be easily plugged through Anderson connector.

Easy maintenance





Removing the strong cover allow to have the access to electric and hydraulic system as to the motorwheel and stabilizing wheels.

Operator platform

The LX stacker can be equipped with cushioned stand-on foldable platform very useful for covering medium-sized distances and for intensive application.

The images are purely indicative.

Product features:

Drive: Electric

Operator type: Pedestrian

Load capacity (Kg): 1600

Load centre distance (mm): 600

Load axle to end forks (mm): 820

Wheel base (mm): 1436

Service weight (Kg): 1050

Axle load, laden rear (Kg): 1673

Axle load, laden front (Kg): 977

Axle load, unladen front (Kg): 723

Axle load, unladen rear (Kg): 315

Tyres: front wheels: RUBBER

Tyres: stabilizers wheels: POLY.C.

Tyres: rear wheels: POLY.C.

Diameter steering wheels (mm): 250

Width steering wheels (mm): 101

Diameter load rollers (mm): 82

Width load rollers (mm): 70

Diameter stabilizers wheels front (mm): 100

Width stabilizers wheels front (mm): 38

Quantity rear wheels: 4

Quantity front wheels: 1 driven

Tread front (mm): 586

Tread rear (mm): 390

Height mast lowered (mm): 1965

Lift height (mm): 2810

Height mast extended (mm): 3370

Height of tiller in drive position max (mm): 1390

Height of tiller in drive position min (mm): 990

Height lowered (mm): 90

Overall lenght (mm): 1944

Overall lenght with lowered platform (mm): 2528





Overall length with raised platform (mm): 2068
Length to face of forks (mm): 795
Length to face of forks with lowered platform (mm): 1378
Length to face of forks with raised platform (mm): 919
Overall width (mm): 800
Thickness fork (mm): 70
Width fork (mm): 170
Length fork (mm): 1150
Fork carriage width (mm): 644
Distance between fork arms (mm): 560
Ground clearance at centre of wheelbase (mm): 20
Aisle width (mm): 2365
Aisle width with lowered platform (mm): 2948
Aisle width with raised platform (mm): 2494
Turning radius (mm): 1613
Turning radius with lowered platform (mm): 2196
Turning radius with raised platform (mm): 1742
Travel speed laden (Km/h): 6
Travel speed unladen (Km/h): 6
Travel speed laden with platform in lowered position (Km/h): 6
Travel speed unladen with platform in lowered position (Km/h): 6
Travel speed laden with platform in raised position or with raised forks (Km/h): 6
Travel speed unladen with platform in raised position or with raised forks (Km/h): 6
Lifting speed laden (m/s): 0.13
Lifting speed unladen (m/s): 0.25
Lowering speed laden (m/s): 0.31
Lowering speed unladen (m/s): 0.38
Max gradeability laden (%): 5
Max gradeability unladen (%): 10
Drive motor power (KW): 1.2
Lift motor power (KW): 3.2
Battery voltage (V): 24
Battery capacity min (Ah): 225
Battery capacity max (Ah): 300
Battery weight min (Kg): 270
Battery weight max (Kg): 270
Energy consumption according to VDI cycle (KWh/h): 1.17
Sound level at driver's ear: 67
Type of lifting: Electric

