



PRAMAC LIFTER HAND PALLET TRUCK GS30S4 1150x525 DOUBLE ROLLER

Product description:

Pramac Lifter GS30S4 1150x525 cm Pallet Truck

The PRAMAC Lifter GS30S4 1150x525 cm pallet truck is the entry level model to the hand pallet truck range with which it shares the characteristics of reliability and robustness.

The PRAMAC Lifter GS30S4 1150x525 cm is the practical and suitable solution for all manual handling needs and is equipped as standard with start and exit rollers with an ergonomically cut handle.

The PRAMAC Lifter GS30S4 is ideal when you don't have to handle large amounts of material every day. The PRAMAC Lifter GS30S4 pallet truck for sale in our catalog is Made in Italy.

The PRAMAC Lifter GS30S4 is built with 1150x525 cm forks and four rear wheels. This pallet truck has a capacity of 3000 kg with a lifting height of 115 mm. The stowage aisle is 1835 mm while the turning radius is 1367 mm.

When the maximum load capacity is exceeded, the oil pressure exceeds its maximum limit and the valve automatically blocks the forks. This prevents possible structural damage.

The frame, after an appropriate conditioning operation, is painted with polyester powder at a temperature of 250° to ensure maximum resistance to wear and tear and atmospheric agents.

TECHNICAL FEATURES PRAMAC Lifter GS30S4 1150x525

Propulsion Type: Manual

Driving System: Accompaniment

Load capacity: 3000 kg

Quantity of rear wheels: 4

Lifting height: 115 mm





Total length: 1550 mm
Total width: 525 mm
Fork width: 150 mm
Fork length: 1150 mm
Width between forks: 525 mm
Storage aisle: 1835 mm
Turning radius: 1367 mm

Are you looking for a pallet truck with different technical characteristics? Here you can find the area dedicated to PRAMAC pallet trucks or other specialized brands

Pictures and technical data are not binding

Product features:

Drive: Manual
Operator type: Pedestrian
Load capacity (Kg): 3000
Load centre distance (mm): 600
Load axle to end forks (mm): 932
Wheel base (mm): 1192
Service weight (Kg): 88
Axle load, laden rear (Kg): 2196
Axle load, laden front (Kg): 892
Axle load, unladen front (Kg): 59
Axle load, unladen rear (Kg): 29
Tyres: front wheels: POLY.I. / NYLON
Tyres: rear wheels: NYLON
Diameter steering wheels (mm): 200
Width steering wheels (mm): 55
Diameter load rollers (mm): 82
Width load rollers (mm): 60
Quantity rear wheels: 4
Rear balancing axle: No
Tread front (mm): 155
Tread rear (mm): 375
Lift height (mm): 115
Height of tiller in drive position max (mm): 1160
Height lowered (mm): 85
Overall length (mm): 1550
Length to face of forks (mm): 400
Overall width (mm): 525
Thickness fork (mm): 50





Width fork (mm): 150

Lenght fork (mm): 1150

Distance between fork arms (mm): 525

Ground clearance at centre of wheelbase (mm): 35

Aisle width (mm): 1835

Turning radius (mm): 1367

Lifting speed laden (strokes): 13

Lifting speed unladen (strokes): 13

Weigher: No

