



PRAMAC LIFTER ELECTRIC PALLET TRUCK CX12 800x520 GEL

Product features:

Drive: Electric

Operator type: Pedestrian

Load capacity (Kg): 1200

Load centre distance (mm): 400

Load axle to end forks (mm): 536

Wheel base (mm): 769

Service weight (Kg): 154

Axle load, laden rear (Kg): 1017

Axle load, laden front (Kg): 337

Axle load, unladen front (Kg): 125

Axle load, unladen rear (Kg): 29

Tyres: front wheels: RUBBER

Tyres: stabilizers wheels: POLY.I.

Tyres: rear wheels: NYLON

Diameter steering wheels (mm): 186

Width steering wheels (mm): 50

Diameter load rollers (mm): 82

Width load rollers (mm): 82

Diameter stabilizers wheels front (mm): 75

Width stabilizers wheels front (mm): 32

Quantity rear wheels: 2

Quantity front wheels: 1 driven

Tread front (mm): 369

Tread rear (mm): 371

Lift height (mm): 115

Height of tiller in drive position max (mm): 1345

Height of tiller in drive position min (mm): 885

Height lowered (mm): 85





Overall length (mm): 1160
Length to face of forks (mm): 360
Overall width (mm): 520
Thickness fork (mm): 55
Width fork (mm): 150
Length fork (mm): 800
Distance between fork arms (mm): 520
Ground clearance at centre of wheelbase (mm): 30
Aisle width (mm): 1382
Turning radius (mm): 918
Travel speed laden (Km/h): 4.3
Travel speed unladen (Km/h): 4.8
Lifting speed laden (m/s): 0.03
Lifting speed unladen (m/s): 0.04
Lowering speed laden (m/s): 0.05
Lowering speed unladen (m/s): 0.02
Max gradeability laden (%): 10
Max gradeability unladen (%): 25
Service brake: Electric
Drive motor power (KW): 0.35
Lift motor power (KW): 0.4
Battery voltage (V): 24
Battery capacity min (Ah): 40
Battery capacity max (Ah): 40
Battery weight min (Kg): 25
Battery weight max (Kg): 40
Energy consumption according to VDI cycle (KWh/h): 0.28
Sound level at driver's ear: 67

