



PRAMAC LIFTER ELECTRIC PALLET TRUCK CX14 1000x525

Product features:

Drive: Electric

Operator type: Pedestrian

Load capacity (Kg): 1400

Load centre distance (mm): 500

Load axle to end forks (mm): 785

Wheel base (mm): 1045

Service weight (Kg): 203

Axle load, laden rear (Kg): 1042

Axle load, laden front (Kg): 561

Axle load, unladen front (Kg): 169

Axle load, unladen rear (Kg): 34

Tyres: front wheels: RUBBER

Tyres: stabilizers wheels: POLY.C.

Tyres: rear wheels: POLY.C.

Diameter steering wheels (mm): 250

Width steering wheels (mm): 76

Diameter load rollers (mm): 82

Width load rollers (mm): 60

Diameter stabilizers wheels front (mm): 100

Width stabilizers wheels front (mm): 40

Quantity rear wheels: 2

Tread front (mm): 506

Tread rear (mm): 375

Lift height (mm): 115

Height of tiller in drive position max (mm): 1242

Height lowered (mm): 85

Overall length (mm): 1500

Length to face of forks (mm): 500

Overall width (mm): 720

Thickness fork (mm): 50





Width fork (mm): 150
Lenght fork (mm): 1000
Distance between fork arms (mm): 525
Ground clearance at centre of wheelbase (mm): 35
Aisle width (mm): 1700
Turning radius (mm): 1285
Travel speed laden (Km/h): 4.5
Travel speed unladen (Km/h): 4.7
Lifting speed laden (m/s): 0.02
Lifting speed unladen (m/s): 0.03
Lowering speed laden (m/s): 0.04
Lowering speed unladen (m/s): 0.04
Max gradeability laden (%): 5
Max gradeability unladen (%): 10
Service brake: Electric
Drive motor power (KW): 0.7
Lift motor power (KW): 0.4
Battery voltage (V): 24
Battery capacity min (Ah): 70
Battery capacity max (Ah): 70
Battery weight min (Kg): 32
Battery weight max (Kg): 32

