



---

# BM2 HOT AIR GENERATOR GP65A

**Product price:**

**550,00 € tax excluded**

**Product description:**

BM2 HOT AIR GENERATOR GP65A

BM2 GP65A is an automatic start LPG-fuelled hot air generator, perfect for heating closed but ventilated rooms such as construction sites, greenhouses and farms.

BM2 GP65A is powered by high-pressure LPG, equipped with an integrated, direct-burning burner. The BM2 GP65A hot air generator is made with automatic ignition thanks to a flame control device, which allows the connection of a thermostat to control ignition and shutdown. For their power supply they are usually connected to LPG cylinders, which makes them handy and very economical.

The BM2 GP65A hot air generator comes complete with:

- Built-in LPG burner
- Safety thermostat
- Electronic flame control with ionization detection
- Power cord with plug
- Socket for connection to thermostat, humidistat or timer
- Complies with UNI EN 1596:2008

**TECHNICAL FEATURES BM2 GP65A**

Maximum heat output: 66.25 KW / 56965 kcal/h / 226055 BTU/h

Minimum heat output: 32.33 KW / 27800 kcal/h / 110315 BTU/h

Power supply: LPG

Maximum gas consumption: 4.268 Kg/h

Minimum gas consumption: 2.097 Kg/h

Gas pressure: 1.5 - 0.4 bar

Efficiency: 100 %

Air flow rate: 1950 m<sup>3</sup>/h

Air temperature at 20°C: 87 °C





Electrical power: 140 W  
Voltage: 230 V  
Phase: Single phase  
Frequency: 50 Hz  
Width: 580 mm  
Length: 317 mm  
Height: 538 mm  
Dry weight: 14 Kg

Are you looking for a hot air generator with different technical characteristics? Here you can find the full range of BM2 hot air generators or other specialized brands.

Images and technical data are not binding and may be subject to revisions by the manufacturer.

**Product features:**

Phase: Single phase  
Fuel: LPG  
Frequency (Hz): 50 / 60  
Voltage (V): 230  
Max rated heat power: 66.25 KW - 56965 Kcal/h - 226055 BTU/h  
Min rated heat power: 32.33 KW - 27800 Kcal/h - 110315 BTU/h  
Max Gas consumption (Kg/h): 4.268  
Min Gas consumption (Kg/h): 2.097  
Gas pressure (bar): 1.5÷0.4  
Heat efficiency (%): 100  
Air flow (m<sup>3</sup>/h): 1950  
Air temperature at 20°C (°C): 87  
Power consumption (W): 140  
Length (mm): 580  
Width (mm): 317  
Height (mm): 538  
Dry weight (Kg): 14

