



---

# BM2 FORCED AIR SPACE HEATERS EK 30 C

**Product price:**

**1.539,00 € tax excluded**

**Product description:**

## BM2 FORCED SPACE HEATERS EK 30 C

BM2 EK30C is a professional/industrial electric hot air generator, replacing the burner with electric resistances which guarantee the heating of the air conveyed by the fan.

BM2 EK30C thanks to its electric generator, you can use it in any environment, professional or residential. Its professional armored heating elements allow the BM2 EK30C generator to work for a long time without creating any problem. It can stay on for days without overheating.

- AISI 321 profile-wound armored heating elements with high heat exchange
- Built-in room thermostat
- Selector switch
- Safety thermostat with manual reset
- Front stainless steel grid
- Can be canalized up to 6 m
- Possibility of stacking
- External thermostat socket

## TECHNICAL FEATURES BM2 EK30C

Maximum power: 30 KW

Maximum rated thermal power: 25818 - 102455 kcal/h - BTU/h

Minimum power: 20 KW

Minimum rated thermal power: 17212 - 68304 kcal/h - BTU/h

Efficiency: 100 %

Air flow rate: 3900 m<sup>3</sup>/h

Thermal rise: 56 - 38 at 20°C

Maximum current: 43 - 28 A

Voltage: 400 V

Phase type: Three-phase

Frequency: 50/60 Hz





Quantity per pellet: 6 pcs

Width: 795 mm

Length: 540 mm

Height: 706 mm

Dry weight: 38 Kg

Looking for a hot air generator with different characteristics? Here you can find the full range of BM2 heaters or other specialized brands

Images and technical data are not binding and may be subject to revision by the manufacturer

**Product features:**

Phase: Three phase

Frequency (Hz): 50 / 60

Voltage (V): 400

Max rated heat power: 30 KW - 25818 Kcal/h - 102455 BTU/h

Min rated heat power: 20 KW - 17212 Kcal/h - 68304 BTU/h

Heat efficiency (%): 100

Air flow (m<sup>3</sup>/h): 3900

Temperature rise at 20°C (°C): 56 - 38

Current max (A): 43 - 28

Length (mm): 795

Width (mm): 540

Height (mm): 706

Dry weight (Kg): 38

