



PRAMAC LIFTER ELECTRIC STACKER RX10/09

Product price:

4.069,00 € tax excluded

Product features:

Drive: Electric
Operator type: Pedestrian
Load capacity (Kg): 1000
Load centre distance (mm): 600
Load axle to end forks (mm): 786
Wheel base (mm): 1165
Service weight (Kg): 337
Axle load, laden rear (Kg): 932
Axle load, laden front (Kg): 405
Axle load, unladen front (Kg): 240
Axle load, unladen rear (Kg): 97
Tyres: front wheels: RUBBER
Tyres: stabilizers wheels: POLY.C.
Tyres: rear wheels: POLY.C.
Diameter steering wheels (mm): 186
Width steering wheels (mm): 50
Diameter load rollers (mm): 82
Width load rollers (mm): 70
Diameter stabilizers wheels front (mm): 125
Width stabilizers wheels front (mm): 45
Quantity rear wheels: 2
Tread front (mm): 505
Tread rear (mm): 410
Height mast lowered (mm): 1270
Normal free lifting (mm): 810
Lift height (mm): 810
Height mast extended (mm): 1270
Height of tiller in drive position max (mm): 1365
Height of tiller in drive position min (mm): 930





Height lowered (mm): 90
Overall length (mm): 1675
Length to face of forks (mm): 522
Overall width (mm): 794
Thickness fork (mm): 60
Width fork (mm): 150
Length fork (mm): 1153
Fork carriage width (mm): 650
Distance between fork arms (mm): 560
Ground clearance at centre of wheelbase (mm): 20
Aisle width (mm): 2120
Turning radius (mm): 1344
Travel speed laden (Km/h): 3.7
Travel speed unladen (Km/h): 4.3
Lifting speed laden (m/s): 0.11
Lifting speed unladen (m/s): 0.18
Lowering speed laden (m/s): 0.18
Lowering speed unladen (m/s): 0.18
Max gradeability laden (%): 9
Max gradeability unladen (%): 25
Service brake: Electric
Drive motor power (KW): 0.35
Lift motor power (KW): 2.2
Battery voltage (V): 24
Battery capacity min (Ah): 70
Battery capacity max (Ah): 70
Battery weight min (Kg): 32
Battery weight max (Kg): 32
Energy consumption according to VDI cycle (KWh/h): 0.45
Sound level at driver's ear: 63
Type of lifting: Electric

