



MOSA GE 90 FSX

Product price:

18.470,41 € tax excluded

Product description:

MOSA GE90 FSX 52,8 KW generating set

MOSA GE90 FSX three-phase power generator of 52,8 KW with Iveco diesel engine. The MOSA GE90 FSX generator set is equipped with electric start. The alternator of the MOSA GE90 FSX generator set is synchronous, three-phase, self-excited, self-regulated, brushless with class H insulation with AVR voltage regulator.

This MOSA is compact and convenient to maneuver and transport thanks to its compact size, with a weight of 1580 kg in addition to its practical pierceable base. The MOSA GE90 FSX generator set with 230 liters fuel tank has a fuel consumption of 14,3 liters/hour at 75% of the load for a 16 hours autonomy.

Technical specifications:

Three-phase Stand-by Output (LTP): 90 kVA (72 kW) /400V / 130A

Three-phase PRP Output: 83 kVA (66.4 kW) / 400V / 120A

Three-phase COP Output: 66 kVA (52.8 kW) / 400V / 95.3A

Frequency 50 Hz

Cos φ: 0.8

ENGINE TECHNICAL DATA

Model: FPT NEF45 SM3

Net stand-by output: 81 kW (110 hp)

Net PRP output: 73.3 kW (100 hp)

Net COP output: 58.4 kW (79 hp)

Cylinders/Displacement: 4 / 4500 cm³ (4. 5 lt.)

Bore / Stroke: 104 / 132 (mm)

Compression Ratio: 17.5: 1

BMEP (Effective Average Pressure: 1777 kPa - 1617 kPa

RPM Controller: Mechanical

110 % (Standby Power): 21. 2 lt./h - 215.8 g/kWh

100 % PRP: 19.4 lt./h - 216.7 g/kWh

75 % PRP: 14.3 lt./h - 215.4 g/kWh





50 % PRP: 9.6 lt./h - 214. 4 g/kWh

Cooling system: Liquid

Total capacity - engine only: 10 lt - 8.5 lt.

Fan air flow: 132 m³/min.

Total oil capacity: 12.8 l

Oil capacity in sump: 8.5 lt. ÷ 5.5 lt.

Oil consumption at full load: Maximum exhaust gas flow: 5.75 kg/mim.

Maximum exhaust gas temperature: 516 °C

Maximum back pressure: 5 kPa (0.05 bar)

Electrical system: 12 Vdc

Starter motor power: 3 kW

Alternating capacity. battery charge: 90 A

Cold start: - 10 °C

With cold start device: - 25°C

Air filter: Dry

Combustion air flow: 7.1 m³/min

From exhaust: 543 kcal/kWh

From water and oil: 412 kcal/kWh

Injected into the environment: 335 kcal/kWh

TECHNICAL DATA ALTERNATOR

Continuous power: 85 kVA

Standby power: 94 kVA

Three-phase voltage: 380 - 415 Vac

Frequency: 50 Hz

Cos ? : 0.8

A.V.R. model. : MARK V

Voltage regulation accuracy: ± 0.5 %

Sustained short-circuit current: 3 In

Transient Cdt (100% of load): Response time: Yield at 100% load 91 %: (400V - Cos ? 0.8)

Isolation: Class H

Connection - Terminals: Star - No. 12

Electromagnetic compatibility: EN 55011

Harmonic distortion - THD: Telephone interference - THF: Direct synchronous - Xd: 285 %

Direct transitory - X'd: 22. 5 %

Direct subtransitory - X'd: 10.8 %

Synchronous quad. - Xq: 160 %

Subtrans. in quadrature - X'q: 12 %

Of reverse sequence - X2: 11.4 %

Of zero sequence - X0: 2.5 %

Transitory - T'd: 0.071 sec

Subtransitory - T'd: 0.005sec

Unidirectional - T'do: 0. 82sec

Unidirectional - Ta / Armatures - Ta: 0.005sec

Short-circuit ratio Kcc: 0.38





Protection class: IP 23

Cooling air flow rate: 0.31 m³/sec.

Coupling | Bearings: Direct SAE 3 -11 ½ - No. 1

GENERAL SPECIFICATIONS

Tank capacity: 230 lt.

Autonomy (75% of PRP): 116 h

Acoustic power measured LwA: 92 dB(A) (67 dB(A) @ 7m)

Acoustic power guaranteed LwA: 94 dB(A) (69 dB(A) @ 7m)

Performance class: G3

Length: 2630 mm

Width: 1130 mm

Height: 1750 mm

Weight: 1580 Kg

MOSA GE90 FSX - Iveco diesel engine electric start - Three-phase alternator - Three-phase power 83 kVA (66.4 kW)

Features:

- Electronic voltage regulation AVR
- Version also available with STAGE 3A engine
- Sealed crankcase able to contain any leakage of liquids present in the engine avoiding environmental pollution
- Oil extraction pump
- Fuel pre-filter with water decanter
- Large access doors to allow easy maintenance (replacement of air, oil, fuel filters)
- Central lifting hook
- Control panel with digital control unit in Automatic or Manual version
- Ready for a wide range of equipment
- Supersilenced
- Complies with EC directives for noise and safety

If you are looking for another product like the Generator Set MOSA GE90 FSX then you can see on our catalog other terrestrial generators.

Images and technical data are not binding.

Product features:

Phase: Single phase / Three phase

Maximum power three phase (KW): 52.8

Continuous power three phase (KW): 48

Maximum power three phase (KVA): 90





Continuous power three phase (KVA): 66

Fuel: Diesel

Frequency (Hz): 50

Voltage (V): 230 / 400

Engine: FPT NEF45 SM3

Emissions Regulations: Stationary Use

Engine rpm (rpm): 1500

Speed governor: Mechanical

Starting system: Electric

Engine capacity (cm³): 4500

Number cylinders: 4

Oil capacity (L): 12.8

Cooling: Water

Inyección : Direct

Alternator: Three-phase synchronous self-excited, self-regulated, brushless

Bore x stroke (mm): 104 x 132

Fuel tank capacity (L): 230

Consumption (L/h): 14.38 at 75% of the load

Running time (h): 16 at 75% of the load

Acoustic power: 94 dB(A)

Acoustic pressure: 69 dB(A) at 7 m

Length (mm): 2630

Width (mm): 1130

Height (mm): 1750

Dry weight (Kg): 1580

Silenced: Yes

Super silenced: Yes

Product type: Generator

ATS Switch device : Optional

Voltage regulator: AVR

Engine manufacturer: FPT Iveco

