



# CGM 12.5DET - COFANATO CON CENTRALINA MANUALE

## Product description:

## Product features:

Phase: Single phase / Three phase

Maximum power three phase (KW): 11

Continuous power three phase (KW): 10

Maximum power three phase (KVA): 13.8

Continuous power three phase (KVA): 12.5

Fuel: Diesel

Frequency (Hz): 50

Voltage (V): 230 / 400

Sockets configuration: 1 x 400V 32A 5P CEE - 1 x 230V 16A 3P CEE

Engine: KOHLER 25LD 330/2

Engine rpm (rpm): 3000

Starting system: Electric

Engine capacity (cm<sup>3</sup>): 851

Number cylinders: 2

Oil capacity (L): 1.7

Cooling: Air

Alternator: With brushes

Poles: 2

Protection degree: IP55

Fuel tank capacity (L): 10

Consumption (L/h): 2.8 at 75% of the load

Running time (h): 3.6

Acoustic pressure: 70 dB(A) at 7 m

Length (mm): 1200

Width (mm): 690

Height (mm): 840





Shop name

---

Dry weight (Kg): 235

Silenced: Yes

Super silenced: Yes

ATS Switch device : No

Voltage regulator: Compound

Engine manufacturer: Kohler



PrestaShop