



# SCHENKER SMART 30 BASIC - NAUTICAL WATERMAKER WITH FLOW RATE 30 LT/H

**Product price:**

**5.092,00 € tax excluded**

**Product description:**

SCHENKER SMART 30 BASIC WATERMAKER 30 LT/H

The Schenker SMART 30 BASIC is a quiet, compact, lightweight, efficient, and affordable marine watermaker. It can be installed in any position, either horizontally or vertically. The indicated flow rates are nominal and may vary by  $\pm 20\%$  depending on actual operating conditions.

The power consumption of the Schenker SMART 30 BASIC marine watermaker is up to 80% lower compared to traditional systems. For example, to produce 60 liters/hour of fresh water, only 240 W are required. The normal engine recharge is therefore more than sufficient to replenish the energy consumed, without the need for a generator.

Thanks to its 80% reduced power consumption and no need for a generator, the CO2 emissions required for water production are reduced by more than 85%. Only Schenker allows you to make water while truly respecting the environment.

Its use is extremely simple, as no manual adjustments are required. All systems are equipped with automatic pressure regulation, meaning no direct access to the watermaker is needed. All functions are managed remotely through the control panel.

The Schenker SMART 30 BASIC does not use high-pressure pumps. The result is extremely quiet operation with no vibrations. The parts in contact with seawater are mainly made of carbon fiber or acetal resin, making the Schenker watermaker completely corrosion-free for life.

In the 2.0 systems, all components subject to wear, such as o-rings and traditional hydraulic seals, have been eliminated. The sealing and sliding elements are made with innovative nanotechnology pads, offering abrasion resistance up to 15 times greater than steel.





The ERS is specifically designed for marine applications and is made with materials completely resistant to brackish water. Moving parts are minimized thanks to the patented solution that eliminates the need for pilot valves.

The kit includes:

- Watermaker with Energy Recovery System
- Feed pump with seawater filter
- Activated carbon filter with solenoid valve
- Seawater intake strainer
- Filter wrench
- Non-return valve
- Freshwater production hose (5 meters)
- Remote control panel
- Installation kit (assorted screws and fittings)
- User manual

**TECHNICAL SPECIFICATIONS SCHENKER SMART 30 BASIC**

Power: 110 W

Power supply: 12 / 24 VDC

Flow rate: 30 L/h

Membranes: 1 x 2.5" x 21"

Control panel: Basic

Length: 715 mm

Width: 265 mm

Height: 249 mm

Weight: 25 kg

Looking for a marine watermaker similar to the SCHENKER SMART 30 BASIC but with different features? [CLICK HERE](#) to explore our full range.

**Product features:**

Power (W): 110

Length (mm): 715

Width (mm): 265

Height (mm): 249

Feed Type: 12 / 24 VDC

Production for hour at 25°C (Lt/h): 30

Daily production at 25°C (Lt/day): 720

Membranes: n.1 2.5" x 21"





---

Remote panel: Basic  
Weight (Kg): 0.4

