



Genmac GR2000iN 1800 Watts Petrol Generator

Product description:

GENMAC GR2000IN SINGLE-PHASE 1,8KW CURRENT GENERATOR WITH INVERTER

The generator **Genmac GR2000iN** single-phase is capable of delivering a maximum power of 1,8KW, super quiet thanks to the inverter supplied.

The Genmac generator with maximum power of 1,8Kw is powered by gasoline with a 4-stroke engine. Particularly compact and light, it can be transported by hand, with extreme ease in any place; this feature, is very appreciated by those customers who sell products in squares, streets or markets and who for reasons of lack or distance of parking for their car, must carry the generator by hand for considerable distances (historic center, disadvantaged areas, etc.).

The 1,8KW generator, has an internal fuel tank with a capacity of 4 lt, the ideal amount to ensure the autonomy necessary for the activity carried out by the user, during the working day, without having the thought of fuel tuck.

The small size and the sturdy handle located above the machine body, make it perfect for transport and easy placement during periods of non-use. All the materials used for the manufacture of Genmac generators, are of first choice, offering and guaranteeing the customer a tested and tested product at a really convenient price. Precisely for this reason, it is a tool much appreciated by professionals and DIY lovers.

Thanks to the Inverter technology's electrical stabilizer that works at very low distortion, the generator delivers constant running loads without voltage spikes that could damage electrical and electronic devices.

A further advantage of the inverter, is to work with variable rpm, according to the need of current to be delivered, optimizing the best fuel consumption, gas emission and wear of mechanical parts. Ideal product for use in campsites, campers and for outdoor leisure time.

Thanks to the low acoustic impact obtained thanks to the inverter, it is possible to use the 1,8KW generator, even in environments where particularly loud noises cannot be accepted, such as historical centers, hospitals, schools, gyms, etc.. Not to be underestimated also the considerable





discomfort that you feel, to be all day long close to noisy generators for work needs.

Technical features of Genmac Generator GR2000iN:

Power supply: Petrol

Inverter synchronous alternator

Single-phase

Continuous power: 1,6KW

Continuous power: 1,6KVA

Maximum power: 1,8KW

Maximum power: 1,8KVA

Voltage: 230V

Frequency: 50 Hz

12V output: 8 A

Degree of protection: IP32

3000 rpm

Tank: 4 Lt.

Autonomy @ 75%: 5.5 h fixed rpm/ 6 h variable rpm

Starting: manual recoil starter

Sockets: 1 schuko+thermal

1 DC 12V + CB output

Length (mm): 498

Width (mm): 290

Height (mm): 459

Dry weight (Kg): 22

Noise level dB(A): 65 @ 7 m

Discover the full range of industrial and portable power generators in the dedicated section.

Images and technical data are not binding and may be subject to review.

Product features:

Phase: Single phase

Maximum power single phase (KW): 1.8

Continuous power single phase (KW): 1.6

Maximum power single phase (KVA): 1.8

Continuous power single phase (KVA): 1.6

Fuel: Gasoline

Frequency (Hz): 50

Voltage (V): 230

Sockets configuration: 1 Shucko + Thermal

Engine: 4 stroke





Engine rpm (rpm): 3000

Ignition: Recoil

Starting system: Manual

Number cylinders: 1

Cooling: Air

Alternator: Synchronous

Protection degree: IP32

Fuel tank capacity (L): 4

Consumption (L/h): 0.62 @ 75%

Running time (h): 5.5 at 75% of the load

Acoustic pressure: 65 dB(A) at 7 m

Length (mm): 498

Width (mm): 290

Height (mm): 459

Dry weight (Kg): 22

Silenced: Yes

Super silenced: Yes

ATS Switch device : No

Voltage regulator: Inverter

