



Genmac G6000ATS Gasoline Generator 6000 Watt AVR

Product price:

780,00 € tax excluded

Product description:

GENERATOR GENMAC G6000ATS SINGLEPHASE WITH AVR

The generator Genmac G6000ATS singlephase is powered by a gasoline engine and can deliver a maximum power of 6KW, including AVR.

The 6KW singlephase generator is equipped with high quality components, it is lightweight, compact, with a modern design and very easy to transport. The 5KW singlephase generator is equipped with a manual rope starter.

The 6KW singlephase generator has been specially developed for camping, caravans, houses, and hobby applications, etc., for this reason it reflects the peculiar features and comfort that allow its reliability and comfort in the fields of application.

The standard equipment on the Genmac G6000ATS generator includes a convenient **counter**, **tank** for great autonomy and **IP23 rain protection**, to use it also in case of bad weather.

The advantages of AVR voltage regulator

The automatic voltage regulator, or **AVR** allows the Genmac 6KW singlephase generator to deliver stable energy and therefore be able to connect equipment with delicate electronics such as computers, appliances, smartphones and tablets: the generator set is therefore ideal for home use, camping, hobby and leisure, but also for construction sites and craftsmen.

The AVR voltage regulator and the other quality standard of the alternator with copper windings will provide you with secure and stabilized energy.

TECHNICAL FEATURES OF THE CURRENT GENERATOR GENMAC G6000ATS:





Power supply: Petrol
AVR Synchronous Alternator
Singlephase
Continuous power: 5.5KW
Continuous power: 5.5KVA
Maximum power: 6KW
Maximum power: 6KVA
Voltage: 230V
Frequency: 50 Hz
12V output: 8 A
Degree of protection: IP23
3000 rpm
Tank: 25 Lt.
Autonomy @ 75%: 10 h
Starting: electric starter, battery included
Sockets: 2 schuko + thermal + CEE 32 A
ATS
1 DC 12V + CB output
Length (mm): 684
Width (mm): 562
Height (mm): 557
Dry weight (Kg): 88
Noise level dB(A): 72 @ 7 m

Discover the whole range of industrial and portable power generators in the dedicated section.

Images and technical data are not binding and may be subject to revision.

Product features:

Phase: Single phase
Maximum power single phase (KW): 6
Continuous power single phase (KW): 5.5
Maximum power single phase (KVA): 6
Continuous power single phase (KVA): 5.5
Fuel: Gasoline
Frequency (Hz): 50
Voltage (V): 230
Sockets configuration: 2 SCHUKO + Thermal + 1 CEE 32A
Engine rpm (rpm): 3000
Starting system: Electric
Number cylinders: 1
Cooling: Air





Alternator: Synchronous
Protection degree: IP23
Fuel tank capacity (L): 25
Consumption (L/h): 3.3 at 75% of the load
Running time (h): 7.5 at 75% of the load
Acoustic pressure: 72 dB(A) at 7 m
Length (mm): 684
Width (mm): 564
Height (mm): 557
Dry weight (Kg): 88
Silenced: No
Super silenced: No
ATS Switch device : Yes
Voltage regulator: AVR