



TELWIN MOTOINVERTER 264DCE

Product description:

TELWIN MOTOINVERTER 264DCE MOTORWELDING 8,1KW

TELWIN MOTOINVERTER 264DCE is a motorwelder equipped with a Lombardini 15LD440 engine powered by gasoline, provides a three-phase power of 8.1KW.

TELWIN MOTOINVERTER 264DCE is a petrol driven welder with inverter technology with high frequency permanent magnet alternator for MMA and TIG-DC electrode welding with smear ignition.

TELWIN MOTOINVERTER 264DCE with inverter technology and high-frequency permanent magnet alternator for MMA and TIG-DC electrode welding with spark ignition.

TELWIN MOTOINVERTER 264DCE has flexibility of use with a wide variety of electrodes: rutile, basic, cellulosic, stainless, cast iron, etc. It can also be used as a direct current (DC) generator to power power power tools such as drills, grinders, etc.

Features:

- Automatic block for lack of oil
- Motor overspeed protection
- Continuous adjustment of welding current
- High stability of the current to the variations of the engine revolutions
- Hot start and anti-stick devices
- Arc force adjustment
- Welder-generator selector
- Thermostatic protection.

TECHNICAL FEATURES TELWIN MOTOINVERTER 264DCE

Phase Type: Single-Phase

Power: 8.1 KW

Mechanical Power: 11 Hp

Frequency: 50 Hz

Voltage: 230 V





Welding Current Type: DC
Welding Type: MMA / TIG
No-load Voltage: 113 V
Current Adjustment: 5-230 A
Maximum Current: 200 A
Electrode Diameter: 1.6 - 5 mm
Fuel: Diesel
Engine: Lombardini 15LD440
Boosting: Electric
Length: 1050 mm
Width: 580 mm
Height: 720 mm
Weight: 107 Kg

Are you looking for a welding machine with different technical characteristics? Here you can find the whole range of TELWIN or other specialized brands.

Images and technical data are not binding.

Product features:

Phase: Single phase
Frequency (Hz): 50
Voltage (V): 230
Engine: Lombardini 15LD440
Engine rpm (rpm): 3500
Starting system: Electric
Engine capacity (cm³): 442
Cooling: Air
Power (KW): 8.1
Protection degree: IP23
No-load voltage (V): 113
Regulation current (A): 5 - 230
Diameter electrodes (mm): 1.6 - 5
Type of welding current: DC
Type of welding: MMA / MIG
Current max (A): 200
Fuel tank capacity (L): 5
Acoustic power: 98 dB(A)
Length (mm): 1050
Width (mm): 580
Height (mm): 720
Voltage regulator: Inverter





Weight (Kg): 107

