



TELWIN TECHNOMIG 223 TREQ SYNERGIC 230V + SPOOL GUN

Product description:

Microprocessor controlled MIG-MAG/FLUX/BRAZING/MMA/TIG DC-Lift inverter multiprocess welding machine.

It is particularly suitable for use in body shops and allows the immediate use of three different torches: two standard mig and an optional spool gun.

This feature enables the user to work directly on different materials without any need to change the torch or the wire spool and this confirms Technomig 223 Treq to be the unique solution for any repair or maintenance needs.

The traditional mig torches are suitable for welding steel, HSS high strength steels, stainless steel and mig-brazing of galvanized sheets, while the spool gun torch is specific for aluminium welding even when working far away from the generator.

The quick SYNERGIC regulation of the welding parameters, thanks to the ONE TOUCH LCD SYNERGY technology, makes this product easy to use.

The made-in-Telwin ATC technology achieves with ease excellent welds on thin thicknesses thanks to an advanced control of the arc. The operator can also intervene manually along the arc length: this adjustment means the weld seam can be modified according to the welder's style.

The ONE TOUCH LCD graphic display allows for a better reading of all welding parameters.

Features:

- 17 synergy curves available
- visualization on LCD display of welding parameters
- regulation of: wire speed upslope, electronic reactance, burn-back time, post gas
- choice of 2/4 times, spot operation
- thermostatic, overvoltage, undervoltage, overcurrent, motorgenerator (+/- 5%) protections.

Complete with 2 MIG-MAG torches, SPOOL GUN, cable and clamp.

Not binding images and technical data.

Product features:





Phase: Single phase
Frequency (Hz): 50 / 60
Voltage (V): 230
Efficiency (%): 84
Protection degree: IP23
No-load voltage (V): 78
Regulation current (A): 20 - 220
Diameter electrodes (mm): 1.6 - 4
Ø steel welding wire (mm): 0.6 - 1
Ø inox welding wire (mm): 0.8 - 1
Ø aluminium welding wire (mm): 0.8 - 1
Ø flux cored welding wire (mm): 0.8 - 1.2
Ø brazing wire (mm): 0.8 - 1
Type of welding: Multiprocess
MIG-MAG welding: MIG-MAG/FLUX/BRAZING
Current max (A): 180
Length (mm): 870
Width (mm): 530
Height (mm): 1665
Voltage regulator: Inverter
Weight (Kg): 55

